

FIBER FACEPLATE SUSPENDED PARTICLE DISPLAY

Technical Field

The technical field relates generally to a visual image display, and, in particular, to a visual image display with a fiber-optic faceplate.

Background

The object of fiber-optic faceplate displays is to provide a reflective, i.e., passively illuminated, display device that appears brightly illuminated even in difficult viewing conditions, and with a pleasingly diffuse "paper-like" appearance.

Fiber-optic faceplate displays are described, for example, in United States Patent No. 5,181,130, issued to Hubby, entitled "Fiber Optic Faceplate Liquid Crystal Display," and United States Patent No. 5,329,386, issued to Birecki and Hubby, entitled "Fiber-Optic Faceplate With Tilted Fibers."

U.S. Patent No. 5,181,130, which is incorporated herein by reference, discloses a liquid crystal display (LCD) that includes a layer of liquid crystal material, a fiber-optic faceplate, and one or more polarizers. The fiber-optic faceplate serves to allow ambient light from a much wider range of incident angles to illuminate the LCD, and allows the viewer to position himself so as to avoid front surface glare and still see the display brightly illuminated, even in difficult lighting situations.

Figure 1 shows the fiber-optic faceplate LCD disclosed in U.S. Patent No. 5,181,130. An incident illumination from a single direction will be spread into a hollow cone by the action of individual fibers of a fiber faceplate 119. Upon passage through a liquid crystal cell, the illumination may encounter a mirror 107 that sends the illumination back through the cell without depolarization or attendant loss in intensity. A second passage through the fiber faceplate 119 may result in a second azimuthal diffusion and the same hollow conical far field pattern.

Since the diffusions take place entirely before and entirely after the double passage of the light through the LC cell and polarizers 105(a), 105(b), there is no loss in light due to depolarization. In addition, the volume representing the intensity of light scattered at a given angle is an article of revolution about the normal to the display surface, not about the direction of specular reflection.

1 Thus, U.S. Patent No. 5,181,130 discloses an LCD structure including a fiber-optic faceplate
2 that does not degrade the viewing angle, contrast, or other operating features of the liquid crystal
3 element itself, provides a wider angle over which ambient light is received for the purposes of
4 illumination, and provides that the viewer need not be close to a position that would cause specularly
5 reflected ambient light to fall in the viewer's eyes.

6 The LCD structure taught in U.S. Patent No. 5,181,130 and other patents, however, proved
7 difficult to build and disappointing in performance because of the requirement for polarizers 105 (a),
8 105(b) that must be placed internal to the liquid crystal cell and withstand its subsequent processing,
9 especially the high temperature cure of the polyamide alignment layers. The polarizers 105(a), 105(b)
10 that are marginally suitable typically have poor transmission and low dichroic ratio, resulting in a dim
11 display with poor contrast, thus defeating most of the potential advantages of the fiber-optic faceplate
12 display.

13 **Summary**

14 A fiber faceplate replaces liquid crystal light control elements in fiber-optic faceplate LCDs with
15 suspended particle devices (SPDs), which provide for passive light control without the need for either
16 polarized light or special alignment layers. In this type of device, a fluid containing optically dense
17 particles that are small enough to remain suspended may be placed either in a cell or within small
18 bubbles in a layer of plastic film. The particles are asymmetric in shape in such a way that the apparent
19 optical density of the particles depends strongly upon the particles' orientation. The orientation of the
20 particles within the fluid can be manipulated by the application of an electric field, so that the fluid or
21 film may appear to be transparent to both polarizations of light when the electric field is applied, and
22 opaque when the electric field is removed and the orientation of the particles is allowed to randomize
23 naturally.

24 **Description of the Drawings**

25 The detailed description will refer to the following figures, in which like numerals refer to like
26 elements, and wherein:

27 Figure 1 shows a prior art fiber-optic faceplate LCD;

1 Figures 2(a) and 2(b) illustrate the transparent and opaque states of one type of a SPD film;
2 and

3 Figure 3 illustrates one embodiment of a fiber-optic faceplate SPD of the present invention.

4 **Detailed Description**

5 An improved fiber faceplate replaces the liquid crystal light control element, such as polarizers
6 105(a), 105(b), with SPDs, which provide for passive light control, similar in many ways to liquid
7 crystals, but without the need for either polarized light or special alignment layers. In comparison to the
8 LCDs, the SPDs have higher contrast and brightness, a wider angle of view, a lower estimated
9 production costs, a less complex fabrication procedure, the ability to function over a wider temperature
10 range, and a lower light loss. In this type of device, a fluid containing optically dense particles that are
11 small enough to remain suspended may be placed either in a cell or within small bubbles in a layer of
12 plastic film. The particles are asymmetric in shape in such a way that the particles' apparent optical
13 density depends strongly upon their orientation. The orientation of the particles within the fluid can be
14 manipulated by the application of an electric field, so that the fluid or film may become transparent to
15 both polarizations of light when the electric field is applied, and opaque when the electric field is
16 removed and the orientation of the particles is allowed to randomize naturally. These characteristics
17 make SPDs a nearly ideal replacement for the liquid crystal light control element specified in the fiber-
18 optic faceplate LCD patents, such as U.S. Patent Nos. 5,181,130 and 5,329,386 mentioned above.

19 The optics of the fiber-optic faceplate SPDs provide additional benefits compared to the fiber-
20 optic faceplate LCDs. For example, since both polarizations of incident light are used, the display is
21 at least twice as bright, with all other things being equal, and no internal polarizers are required.
22 Additionally, since no alignment structure is necessary on the fiber-optic faceplate, small amounts of
23 relative motion between s front fiber-optic faceplate and rear substrates can be allowed by using a
24 resilient, or even non-adherent, perimeter seal. This may accommodate a substantial difference in
25 coefficient of thermal expansion between the rear substrate material and the fiber-optic faceplate, which
26 may be necessary due to the limited range of material choices available for both substrates. If color
27 filters are included to produce a color display, the color filters may be located on the rear substrate
28 where the pixel locations are defined. In addition, film-type suspended particle media may be used by

1 optically matching the medium to the front and rear substrates with adhesives and/or non-hardening fluid
2 of the proper index of refraction to allow the two substrates to move slightly with respect to each other,
3 thus accommodating the difference in thermal expansion.

4 SPDs in general are described in United States Patents No. 4,407,565, issued to Saxe, entitled
5 "Light Valve Suspension Containing Fluorocarbon Liquid," United States Patents No. 5,463,491,
6 issued to Check and Bayshore, entitled "Light Valve Employing A Film Comprising An Encapsulated
7 Liquid Suspension, And Method Of Making Such Film," and United States Patents No. 5,463,492,
8 issued to Check and Bayshore, entitled "Light Modulating Film Of Improved Clarity For A Light
9 Valve," which are incorporated herein by reference.

10 U.S. Patent No. 4,407,565 discloses a SPD light valve including a cell containing a suspension
11 of particles in a liquid suspending medium.

12 U.S. Patent Nos. 5,463,491 and 5,463,492 disclose a SPD film suitable for use as the light
13 modulating unit of a SPD light valve, including a cross-linked polymer matrix having droplets of a liquid
14 light valve suspension distributed in the cross-linked polymer matrix, and a SPD light valve that includes
15 such a film.

16 The SPD light valve may be described as a cell of fluid or a layer of film formed of two walls
17 that are spaced apart by a small distance, with at least one wall being transparent. The walls may
18 include electrodes in the form of transparent conductive coatings. The fluid or film may contain a liquid
19 light valve suspension of small suspended particles. The liquid light valve suspension means a liquid
20 suspending medium in which a plurality of small particles are dispersed. The liquid suspending medium
21 may include one or more non-aqueous, electrically resistive liquids in which there is preferably dissolved
22 at least one type of polymeric stabilizer that acts to reduce the tendency of the particles to agglomerate
23 and to keep them dispersed.

24 In the absence of an applied electrical field, the particles in the liquid suspension may exhibit
25 random Brownian movement, and hence a beam of light passing into the fluid or film may be reflected,
26 transmitted or absorbed, depending upon the nature and concentration of the particles and the energy
27 content of the light. On the other hand, when an electric field is applied through the liquid light valve
28 suspension in the SPD light valve, the particles may become aligned and for many suspensions most of

1 the light can pass through the fluid or film.

2 As is known, inorganic and organic particles may be used in a light valve suspension, such as
3 mica, metals, graphite, metal halides, polyhalides (sometimes referred to as perhalides) of alkaloid acid
4 salts and the like. The particles in the liquid suspension may be light-polarizing, such as
5 halogen-containing light-polarizing materials, e.g., polyhalides of alkaloid acid salts. (The term "alkaloid"
6 is used herein to mean an organic nitrogenous base, as defined in Hackh's Chemical Dictionary, Fourth
7 Edition, McGraw-Hill Book Company, New York, 1969). If a polyhalide of an alkaloid acid salt is
8 used, the alkaloid moiety may be a quinine alkaloid, as defined in Hackh's Chemical Dictionary, supra.
9 U.S. Patent Nos. 2,178,996 and 2,289,712 refer in detail to the use of polyhalides of quinine alkaloid
10 acid salts. The particles may be light absorbing or light reflecting.

11 Also, the particles may be particles of a hydrogenated polyhalide of a quinine alkaloid acid salt,
12 such as dihydrocinchonidine sulfate polyiodide, as described in U.S. Patent No. 4,131,334, or a
13 light-polarizing metal halide or polyhalide, such as cupric bromide or purplecobaltchloride sulfate
14 polyiodide, as described, for example, in U.S. Patent No. 1,956,867. Preferably, the particles are
15 light-polarizing polyhalide particles such as those described in U.S. Patent Nos. 4,877,313 and
16 5,002,701, which are more environmentally stable than earlier prior art polyhalides.

17 In theory, any type of particle capable of reflecting, absorbing and/or transmitting desired
18 wavelengths of visible light can be used in the liquid light valve suspension. Iodine is widely used for
19 such particles.

20 The shape of the particles used in the light valve suspension should preferably be "anisometric,"
21 i.e., the shape or structure of the particle is such that in one orientation the particle intercepts more light
22 than in another orientation. Particles that are needle-shaped, rod-shaped, lath-shaped, or in the form
23 of thin flakes, are suitable. Light-polarizing crystals are especially useful because they produce a
24 pleasing visual appearance, but any type of light-absorbing particle, preferably exhibiting very little light
25 scatter, can be employed.

26 The particles are preferably of colloidal size, i.e., the particles will have a large dimension
27 averaging about 1 micron or less. Preferably, most particles will have large dimensions less than
28 one-half of the wavelength of blue light, i.e. 2000 Angstroms or less to keep light scatter extremely low.

1 The particles are also preferably light-absorbing, i.e., the particles absorb a significant part,
2 preferably most, of the light impinging on them and scatter relatively little of the light that impinges on
3 them. Light-absorbing particles may include many types of material including colored orientable
4 pigments and dyes, e.g., garnet red, conductive black or grey material such as graphite or carbon black,
5 dichromic dyes such as are widely used in guest-host liquid crystal devices, light-polarizing materials,
6 e.g., cupric bromide, and polyhalides.

7 Referring to Figure 2(a), in a side sectional view of a SPD light valve 227, a beam of light 231
8 impinges on the SPD light valve 227. The SPD light valve 227 may include a layer of SPD fluid or film
9 224 containing light valve suspension droplets 226, and a pair of electrodes 228(a), 228(b) in contact
10 with the opposite surfaces of the layer of SPD fluid or film 224. Protective layers 229 may be
11 positioned in contact with each electrode 228(a), 228(b). If no potential difference, i.e., electric field,
12 exists between the electrodes 228(a), 228(b), suspended particles 233 dispersed within the light valve
13 suspension droplets 226 may be in random positions due to Brownian movement. Because the
14 particles 233 absorb light, the beam of light 231 impinging on the SPD light valve 227 may be absorbed
15 by the particles 233 within the light valve suspension droplets 226.

16 Referring to Figure 2(b), if an electric field (not shown) is applied between the electrodes
17 228(a), 228(b), the particles 233 may align within the light valve suspension droplets 226, and a
18 considerable portion of the beam of light 231 may pass through the SPD light valve 227 as indicated
19 by the arrows 232.

20 Electrodes 228(a), 228(b) for use in the SPD light valves 227 and methods of depositing
21 electrodes 228(a), 228(b) on glass and plastic substrates 107 are well known in the art. For example,
22 U.S. Patent Nos. 3,512,876 and 3,708,219 disclose use of electrodes in SPD light valves, and U.S.
23 Patent Nos. 2,628,927, 2,740,732, 3,001,901 and 3,020,376 disclose articles having conductive and
24 especially conductive transparent coatings on glass and plastic substrates and methods of forming or
25 depositing such coatings. Indium tin oxide ("ITO") or other conductive metal can be used.

26 The term "electrode" shall be understood to mean not only electrically conductive metal oxide
27 and other coatings used in the art for such purpose but also such coatings that have dielectric
28 overcoatings on them of materials such as silicon monoxide or dioxide, titanium dioxide, aluminum

oxide, tantalum pentoxide, magnesium fluoride, or other materials. The electrodes 228(a), 228(b) may cover all or part of the substrate 107 on which they are located and may also be applied in patterns. For example, in a SPD light valve 227 functioning as a variable light transmission window or filter, one would usually wish to vary the amount of light passing through the entire active area of the device. On the other hand, if the SPD light valve 227 were intended to be used as a display device, the electrodes 228(a), 228(b) would normally be deposited in patterns in discrete areas of the substrate 107. The term "electrode" also includes use of semiconductor films and plural film layers, both transparent and colored, such as are used in active matrix addressed display devices. In all cases where the SPD fluid or film 224 is used in a device, the device includes appropriate electrical connections leading to a power supply suitable to operate the device.

By replacing the LCDs with the SPDs, the optics of the fiber-optic faceplate may produce the same benefits as explained in U.S. Patent No. 5,181,130 without the need for either polarized light or special alignment layers. These benefits may include bright display appearance over a substantial viewing angle range relatively independent of the number and location of illumination sources, a diffuse, paper-like appearance in the light areas of the display, and an image that appears to be on the front surface of the display with which can be interacted by the user with little or no problems due to parallax, i.e., in the case of a touch screen. In addition to these common benefits, the optics of the fiber-optic faceplate with SPDs may be more practical than the LCDs taught in U.S. Patent No. 5,181,130.

Figure 3 illustrates one embodiment of a fiber-optic faceplate with a SPD. The front layer (top layer in the drawing) with vertical lines may be a fiber-optic faceplate 119 with a front face (upper face in the drawing) 320(a) and a rear face (lower face in the drawing) 320(b). The fiber-optic faceplate 119 may be made of millions of straight optical fibers 319 that are fused together and whose longitudinal axes are parallel to each other and perpendicular to the upper face 320(a) and the lower face 320(b) of the faceplate 119. Each of the fibers 319 may collect and project through the faceplate 119 light rays impinging from the upper face of the faceplate 119.

The fiber-optic faceplate 119 may be fabricated to a thickness in the range of approximately 0.25 to 5.0 millimeters, preferably about 1.0 millimeters, having individual fibers in the range of, for example, 6 to 50 microns.

1 The rear layer (bottom layer in the drawing) may be a rear substrate 107, such as glass, mirror,
2 or plastic. A thin layer of SPD fluid or film 224 captured in the SPD light valve (cell) 227 may lie
3 between the fiber-optic faceplate 224 and the substrate 107.

4 A pair of conductive electrodes 228(a), 228(b) may be positioned on the inner surface (bottom
5 surface in the drawing) of the faceplate 119 and on the outer surface (top surface in the drawing) of the
6 rear substrate 107. Both the top electrode 228(a) and the bottom electrode 228(b) may be transparent
7 to light and in contact with opposite surfaces of the layer of SPD fluid or film 224, i.e., the layer of SPD
8 fluid or film 224 is positioned between the two electrodes 228(a), 228(b). The bottom electrode
9 228(b) may be made of metals that are good electrical conductors and reflect light well, such as
10 aluminum.

11 If a voltage is applied between these two electrodes 228(a), 228(b), a electric field (not shown)
12 may be established perpendicular to the two electrodes 228(a), 228(b). The electric field may cause
13 a polarization in the suspended particles 233 within the light valve suspension droplets 226, which may
14 develop a dipole moment that opposes the electric field caused by the electrodes 228(a), 228(b). The
15 net effect is that these suspended particles 233 may become aligned, and most of the light coming from
16 the front surface (top surface in the drawing) can pass through the SPD fluid or film 224.
17 Consequently, the SPD fluid or film 224 may appear to be transparent to light. To prevent the particles
18 233 from moving inside the SPD fluid or film 224, an alternating electric field may be generated. The
19 thus-generated alternating electric field eliminates the electrophoresis effect, which causes the dipoles
20 226 in the electric field not only to align but also to move with the electric field.

21 In the absence of an electrical field, the particles 233 in the liquid light valve suspension droplets
22 226 may exhibit random Brownian movement, and hence a beam of light passing into the SPD fluid or
23 film 224 may be reflected, transmitted or absorbed, depending upon the nature and concentration of
24 the particles and the energy content of the light. Consequently, the SPD fluid or film 224 may appear
25 to be opaque.

26 Accordingly, by using electricity, the transmission of light can be controlled efficiently without
27 the need to polarize the light. Since both polarizations of incident light may be used, the display may
28 be at least twice as bright in comparison with the fiber-optic faceplate LCDs, with all other things being

1 equal. Furthermore, internal polarizers 105 (a), 105(b) are not required.

2 A transparent conductive layer 305 for pixel drive may be coated underneath the fiber-optic
3 faceplate 119, and on top of the layer of SPD fluid or film 224. If the SPD film 224 is used, a thin layer
4 of index matching fluid 303 may be coated on top of the SPD film 224.

5 Since no alignment structure is necessary on the fiber-optic faceplate 119, small amounts of
6 relative motion between the front fiber-optic faceplate 119 and the rear substrate 107 can be allowed
7 by using a resilient, or even non-adherent, perimeter seal 309, positioned at the outer edges of the layer
8 of SPD fluid or film 224. The use of the perimeter seal 309 may accommodate a substantial difference
9 in coefficient of thermal expansion between the rear substrate material 107 and the fiber-optic faceplate
10 119, which may be necessary due to the limited range of material choices available for both substrates.
11 If color filters 307 are included to produce a color display, the color filters 307 may be located on the
12 rear substrate 107 where the pixel locations are defined. Film-type suspended particle media may also
13 be used by optically matching it to the faceplate 119 and rear substrate 107 with adhesives and/or non-
14 hardening fluid of the proper index of refraction, allowing the two substrates to move slightly with
15 respect to each other to accommodate the difference in thermal expansion discussed above.

16 While the SPD fiber faceplate has been described in connection with an exemplary
17 embodiment, it will be understood that many modifications in light of these teachings will be readily
18 apparent to those skilled in the art, and this application is intended to cover any variations thereof.